

# WALL LAMP

Wall Lamp | ELX-WL



## Wall Lamp

### ELX-WL



- 3.000K
- 4.000K
- 5.000K
- 6.000K

## ■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Material
6W	AC100-240V	50/60Hz	80Lm/W	240Lm	>80Ra ( <i>&gt;90Ra Optional</i> )	3000K/4000K/6000K	IP65	Die Casting Aluminium
12W	AC100-240V	50/60Hz	80Lm/W	480Lm	>80Ra ( <i>&gt;90Ra Optional</i> )	3000K/4000K/6000K	IP65	Die Casting Aluminium
24W	AC100-240V	50/60Hz	80Lm/W	960Lm	>80Ra ( <i>&gt;90Ra Optional</i> )	3000K/4000K/6000K	IP65	Die Casting Aluminium
36W	AC100-240V	50/60Hz	80Lm/W	2.880Lm	>80Ra ( <i>&gt;90Ra Optional</i> )	3000K/4000K/6000K	IP65	Die Casting Aluminium
48W	AC100-240V	50/60Hz	80Lm/W	3.880Lm	>80Ra ( <i>&gt;90Ra Optional</i> )	3000K/4000K/6000K	IP65	Die Casting Aluminium

Model : ELX-WL90260-03WX2




Dimension ( mm )



Model : ELX-WL90260-06WX2




Dimension ( mm )



Model : ELX-WL110300-12WX2




Dimension ( mm )



Model : ELX-WL145300-18WX2




Dimension ( mm )



Model : ELX-WL160300-24WX2



Dimension ( mm )



Application



\* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

