

Wall Lamp

ELX-WL




3.000K	4.000K	5.000K	6.000K
--------	--------	--------	--------


■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Material
6W	AC100-240V	50/60Hz	80Lm/W	240Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium
12W	AC100-240V	50/60Hz	80Lm/W	960Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium
24W	AC100-240V	50/60Hz	80Lm/W	1.920Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium
36W	AC100-240V	50/60Hz	80Lm/W	2.880Lm	>80Ra (<i>>90Ra Optional</i>)	3000K/4000K/6000K	IP65	Die Casting Aluminium

Model : ELX-WL6363160-03WX2




Dimension (mm)




Model : ELX-WL9090260-06WX2




Dimension (mm)




Model : ELX-WL120120300-12WX2




Dimension (mm)



Model : ELX-WL150150300-18WX2



Dimension (mm)



Application



* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°