



# DOWN LIGHT

Indoor Light | Downlight



## Downlight Ecoluxon ELX-ECDL-COB

120  
Lm/W



3.000K    4.000K    5.000K    6.000K


### ■ Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Berat	Material
5W	AC100-240V	50/60Hz	120Lm/W	600Lm	>80Ra	3000K/4000K/6000K	IP20	30°	93gr	Aluminium Alloy
8W	AC100-240V	50/60Hz	120Lm/W	960Lm	>80Ra	3000K/4000K/6000K	IP20	30°	130gr	Aluminium Alloy
12W	AC100-240V	50/60Hz	120Lm/W	1.440Lm	>80Ra	3000K/4000K/6000K	IP20	30°	238gr	Aluminium Alloy
15W	AC100-240V	50/60Hz	120Lm/W	1.800Lm	>80Ra	3000K/4000K/6000K	IP20	30°	413gr	Aluminium Alloy


Model : ELX-ECDL-COB-5W



Dimension ( mm )




Light Distribution Curve




Model : ELX-ECDL-COB-8W



Dimension ( mm )




Light Distribution Curve




Model : ELX-ECDL-COB-12W



Dimension ( mm )




Light Distribution Curve




Model : ELX-ECDL-COB-15W



Dimension ( mm )



Light Distribution Curve



- \* Easy maintenance
- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

