Downlight

DOWN LIGHT

3.000K | 4.000K | 5.000K | 6.000K

ZERON
NEW LIGHT NEW LIFE

Recessed Downlight

ZERN-Y01KZR

Honeycomb

100 Lm/W

Body Color

Reflector Color

Specification

Daya (W)	Input Voltage	Frequency Amp	LED Efikasi	Total Lumen	CRI	Temperatur Warna	Proteksi	Beam Angle	Material
24W	AC100-240V	50/60Hz	100Lm/W	2.400Lm	>80Ra *Optional (>90Ra, >95Ra)*	3000K/4000K/6000K	IP20	15°/24°/36°	Die Casting Aluminium
32W	AC100-240V	50/60Hz	100Lm/W	3.200Lm	>80Ra *Optional (>90Ra, >95Ra)*	3000K/4000K/6000K	IP20	15°/24°/36°	Die Casting Aluminium
36W	AC100-240V	50/60Hz	100Lm/W	3.600Lm	>80Ra *Optional (>90Ra, >95Ra)*	3000K/4000K/6000K	IP20	15°/24°/36°	Die Casting Aluminium
45W	AC100-240V	50/60Hz	100Lm/W	4.500Lm	>80Ra *Optional (>90Ra, >95Ra)*	3000K/4000K/6000K	IP20	15°/24°/36°	Die Casting Aluminium
48W	AC100-240V	50/60Hz	100Lm/W	4.800Lm	>80Ra *Optional (>90Ra, >95Ra)*	3000K/4000K/6000K	IP20	15°/24°/36°	Die Casting Aluminium
60W	AC100-240V	50/60Hz	100Lm/W	6.000Lm	>80Ra *Optional (>90Ra, >95Ra)*	3000K/4000K/6000K	IP20	15°/24°/36°	Die Casting Aluminium

Model : ZERN-Y01KZR-8W*3



Dimension (mm)



Model : ZERN-Y01KZR-8W*4



Dimension (mm)



Model : ZERN-Y01KZR-12W*3



Dimension (mm)



Model : ZERN-Y01KZR-12W*4



Dimension (mm)



Model : ZERN-Y01KZR-15W*3

Dimension (mm)



Model : ZERN-Y01KZR-15W*4

Dimension (mm)



* Easy maintenance
- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°