



# TRACK LIGHT

Indoor Light | Track Light



## Track Light Ecoluxon

**ELX-W01-XSD**

3.000K    4.000K    5.000K    6.000K


### ■ Specification

| Daya (W) | Input Voltage | Frequency Amp | LED Efikasi | Total Lumen | CRI  | Temperatur Warna        | Proteksi | Beam Angle  | Material              |
|----------|---------------|---------------|-------------|-------------|--|-------------------------|----------|-------------|-----------------------|
| 5W       | AC100-240V    | 50/60Hz       | 85Lm/W      | 425Lm       | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K/6000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 7W       | AC100-240V    | 50/60Hz       | 85Lm/W      | 595Lm       | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K/6000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 9W       | AC100-240V    | 50/60Hz       | 85Lm/W      | 765Lm       | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K/6000K | IP20     | 15°/24°/36° | Die Casting Aluminium |
| 12W      | AC100-240V    | 50/60Hz       | 85Lm/W      | 1.020Lm     | >80Ra <i>Optional (&gt;90Ra, &gt;95Ra)</i> | 3000K/4000K/5000K/6000K | IP20     | 15°/24°/36° | Die Casting Aluminium |

Model : ELX-W01-XSD-5W




Dimension ( mm )



Model : ELX-W01-XSD-9W




Dimension ( mm )



Model : ELX-W01-XSD-7W




Dimension ( mm )



Model : ELX-W01-XSD-12W



Dimension ( mm )



#### Optional Application



\* Easy maintenance

- Modular LED for easy replacement
- Opening and closing possible of LED module part and power supply part
- Customizable beam angle
- Temperature max 50°

